







The flanges division encompasses an integrated forge shop which manufactures various types of pipe fitting i.e. flanges, but welding fittings (stubends) in various specifications (ASME, EN, DIN, AFNOR, AWWA, GOST, BS, JIS, AS, MSS, SA, UNI SABS/SANS,NS,VSM.) as well as forged bars.

Flanges are produced in size ranges from 1/2" to 40".

Viraj has an established and stringent quality system with over 100 approvals / certificates till date in accordance with various specific requirements and applications. These approvals and certifications enable our customers to supply Viraj flanges to major end users across a variety of industries.

Our integrated operations include facilities for cutting, forging, ring rolling and machining with CNC lathes, VMC (machining centre), high capacity forging press and mobile manipulator for making big diameter forged round bars. We also have an in-house heat treatment shop and well equipped laboratory facilities for mechanical and metallurgical testing, PMI testing with X-Ray and Optical Emission Spectroscopy. Also we have fully equipped Radiation Contamination Monitoring facilities.

Industries we serve:

- Pipeline engineering
- ☑ Oil & gas upstream & downstream
- ✓ Mechanical & plant engineering
- Ship building
- ✓ Boiler and Pressure Vessels
- ✓ Fertilizer industry
- ✓ Waste water
- ☑ Chemical & petrochemical
- ✓ Power industries (nuclear, natural gas, wind, solar)
- Aerospace

Makeability Chart:

Specification	Item description	Size Range	Pressure Class
ASME - B16.5	Slip-on flange, Welding neck flange, Blind flange, Threaded flange, Lap joint flange, RTJ flange	½" to 24" ½" to 12	150, 300, 400, 600, 900, 1500 2500
ASME - B 16.47	Welding neck flange, Blind flange	26" to 40" (A-MSS) 26" to 30" (A-MSS) 26" to 36" (B-API) 26" to 30" (B-API)	150, 300, 400, 600, 900, 75, 150, 300, 400, 600 900
ASME - B 16.36	Welding neck flange Slip-on flange, Threaded flange	1" to 24" 1" to 12"	300, 400, 600, 900, 1500, 2500
DIN FLANGE	DIN2512, DIN2513, DIN 2514, DIN2527, DIN 2566, DIN2573, DIN2576, DIN2627, DIN2628, DIN2629, DIN2631, DIN2632, DIN2633, DIN2434, DIN2635, DIN2637, DIN2628, DIN2641, DIN2642, DIN2655, DIN2656, DIN2673	10 to 1000	PN6 to PN 320
Pr EN 1092 – 1	Plate flange (01) Loose plate flange (02, 04) / Blind flange (05) Welding neck flange (11)/ Hubbed slip-on flange (12) Hubbed threaded flange (13)/ Integral flange (21), weld-on collar (32) Lapped pipe end (33) Weldneck coller (34) Welding ring neck (35)	10 to 1000	ISO-PN2.5 to PN100

Specification	Item description	Size Range	Pressure Class
EN 1759 – 1	Plate flange (01)/ Blind flange (05) Welding neck flange (11)/ Hubbed slip-on flange (12) Hubbed threaded flange (13)/ Hubbed socket weld (14) Loose Hubbed flange (15) Integral flange (21)	½" to 24" (15 to 600)	150, 300, 400, 600, 900, 1500 2500 (12")
AFNOR NEF 29-20	Plate flange (01)/Loose plate flange (02, 04)/ 3Blind flange (05) Welding neck flange (11)/ Hubbed Slip-on flange (12) Screwed flange (13) Hubbed socket Welding (14) Loose Hubbed (15)/Integral flange (21)	10 to 600	ISO-PN2.5 to PN420
JIS B2220/B2291	Slip-on plate flange (SOP), Slip-on Hub (SOH), Socket Welding flange (SW), Welding neck flange (WN), Lap joint (LJ), Threaded flange (TR)/ Itegral flange (IT) Blank flange (BL)	10 to 600	5K, 10K, 15K, 20K, 30K
BS4504 SECTION 3.1	Welding neck (111)/Slip-on plate (101)/ Screwed boss (113)/ Slip-on boss (112)/ Blind plate flange (105)	0.375" To 36"	PN2.5 to PN40
BS4504 PART 1	Welding neck (2), Plate slip-on (30), Screwed boss (4), Slip-on boss (5),	0.375" to 36"	PN2.5 to PN 400
BS 1560 SECTION 3.1	Blind plate flange (8) Welding neck (111), Socket weld (114), Screwed boss (113), Slip-on boss (112), Blind flange (105), Lapped flange (115)	½" to 24"	150 LBS to 2500 LBS
BS 10: 1962	Welding neck, Plate Slip-on, Screwed boss, Slip-on boss, Plate blind flange	½" to 36"	TABLE D/E/F/H
SABS/SANS 1123	Integral (1), Welding neck (2), Plate for welding (3), Screwed boss (4), Slip-on boss (5) Plate blank (8)	10 to 1000	250, 600, 1000, 1600, 2500, 4000 kPa
AWWA C228	Ring type Slip-on flanges, Blind flanges	2" to 40"	SA (50Psi), SB (86Psi), SD (150/75Psi), SE (275Psi), SF (300Psi)
Italian standard UNI FLANGES	Plan flanges (2276, 2277, 2278, 6083, 6084) Welding neck (2280, 2281, 2282, 2283, 2284, 2285, 2286) Lapped flanges (6088, 6089, 6090, 2999, 2300) Blind flanges (6091, 6092, 6093, 6094, 6095, 6096, 6097) Threaded flanges (2253, 2254)	15 to 200	PN 6 to PN 40
Norwegian Standard (NS)	Blind flanges, Plain welding flanges	150 to 800	PN 6 to PN 40

Dimensional specifications with size range				
Specification	Item description	Size Range	Pressure Class	
Flanges to VSM	Flat flange for welding (18695, 19696,		PN 6 to PN 16	
(Swiss) Standards	18697) Weld neck (18716, 18718), Blind flange (18703)			
AS 4087	Blank, Plate, Screwed, weld neck	50 to 1000	PN16, PN21,	
AS 2129	(W.N/W.O.N), Integral flange blank, Plate, Boss, Weld neck, Integral flange	15 to 1000	PN35, TABLE D & E	
GOST	Plate flange (GOST 12820-80), Weld neck flange (GOST 12821-80), Blind flange (GOST 12836-67)	10 to 1000	0.6MPa to 6.3 MPa	
ASME/ANSI B 16.9 MASS SP-43	STUB END – TYPE A,B,C (Short pattern)	½" to 24"	All Schedules	

Grade:

ASTM182/182M	F 304, F304L, F304H, F310, F316, F316L, F316H, F347, F347H, F317, F317L, F321H, F316Ti,
ASMESA182/182M ASTM A403/403M	F347, F347H, F51, F60 & F53
ASTM 815/815M	S31803, S32205
JIS G3214	SUS F304, SUS F304L, SUS F304H, SUS F316, SUS F316L, SUS F316H, SUS F347, SUS F347H, SUS F317, SUS F317L, SUS F321, SUS F321H
NF E29 – 204 (AFNOR)	BF Z7 CN 18-09 (F304), BF Z3 CN 19-09 (F304L), BF Z7 CND 17.11.02 (F316), BF Z3 CND 17.11.02 (F316L), BF Z6 CNDT 17-12 (316 Ti), BF Z6 CN Nb 18-10 (F347), BF Z6 CNT 18-10 (F321)
DIN 10222-5	1.4301, 1.4306, 1.4307, 1.4541, 1.4571, 1.4401, 1.4404, 1.4410, 1.4438, 1.4450, 1.4462
OTHER PRODUCTS	Long welding neck, Plate flanges (Light weight pattern), Backup flanges (BEV & STD), Beveled ID flanges, Reducing flanges, Case-end

Flanges bore schedules:

S5S, S10, S10S, S20, S30, S40, S40S, S60, S80, S80S, S100, S120, S140, S160, STD, XS, XXS

Flanges facing types:

Flat face, Raised face, Large Raised face, Ring joint, Tongue & Groove face (large & small), Male-Female face

Flanges face finish:

Stock Finish serration, continuous spiral groove (Phonographic) Serration, concentric Serration, Smooth Finish

Manufacturing facilities:

- ✓ Raw material cutting: band saw
- Open / Close Die Forging & Rolling: Hammer / Press / Ring Rolling
- ✓ Machining: CNC lathes/SPM lathes
- ☑ Bolt Hole drilling: High speed CNC Vertical Machining Center
- ✓ Heat treatment: Solution Annealing (batch annealing furnaces)

Testing facilities:

- ✓ Tensile testing machine (screw driven & Computerized)
- ✓ Impact testing machine (RT & Sub zero)
- Hardness testing machine
- Microscope (Image analyzer with color view camera, motorized stage & inclusion inspector)
- ✓ Mobile spectrometer for PMI test : X-ray fluorescence test-gun & OES-Optical Emission Spectrometry
- ✓ Surface roughness tester
- ✓ IGC test facilities
- Dye penetrate test
- Ultrasonic testing machine
- ✓ Radiation servo meter
 - Dynamic radiation detection system with weighbridge portal monitors
 - Gamma ray spectroscopy identifies nuclides & quantifies contamination
 - Portable radiation detection servo meters

Packing:

- ✓ Protect raised face and bevel end with plastic protection caps
- ✓ Using plywood boxes size 800 x 1200 mm (Euro pallet) for shipment























www.viraj.com

CONTACT US

Corporate Office:

Viraj Tower, 1st Floor, Western Express Highway, Near Land Mark Building, Andheri (East), Mumbai - 400069. India

Tel: +91 22 6276 6200 Fax: +91 22 2683 1313

Regd. Marketing Office:

G-34 MIDC Tarapur Industrial Area, Boisar, Dist. Palghar, Maharashtra - 401 506, India Tel: +91 - (02525) 660 600 Fax: +91(2525) 260 159

Regional Office:

D-7, 2nd Floor, Above Mehrason's Jewellers, Ring Road, South Extension Part II, New Delhi 110049, India. Tel: +91 - 11 40219804

For Product Related Enquiries: sales@viraj.com
For Media, PR & Events: corpcomm@viraj.com